

RETARDER MOUNTS				
Reference	Description	Central Bolt Torque - Nm	Securing Bolts Torque - Nm	Used on
JZ100160	Circular mount with steel outer sleeve	200	20	CC65/50 CC65 CC80 CC100 CC125 CC135 CC160 AC50-65 AC50-80 AC51-00 AC61-25 AC61-35 AC61-60
JZ100170	Circular mount with steel outer sleeve	200	20	CC200 CC250 CC300 C8770 AC72-00 AC82-70 AC83-00 AC83-31
JZ100180	Circular mount with triangular 3-hole steel fixing plate	90	20	C3764 CE30 CE35 CC50 AE30-35 AE30-32 AC50-55
JZ100723	2 Part Circular mount	170		CC65/50 CC65 CC80 CC100 CC125 CC135 CC160 AC50-65 AC50-80 AC51-00 AC61-25 AC61-35 AC61-60 AD61-55 AD72-00
JZ100759	2 Part Circular mount	170		CC200 CC250 CC300 C8770 AC72-00 AC82-70 AC83-00 AC83-31 M-Series
JZ100796	2 Part Circular mount	230		AD50-55 AD50-90

MINIGENERATOR	
Tightening Torque - Nm	20
Operating Temperature Range - °C	-40 to +107
Resistance Ohms +/- 10%	280
Output at 1750 rpm – no load – Volts rms	30